## Swing pump Rexroth A4VG28 DWDT1/32R-NZC10F013D-S R902023012



**Weight:** 34.00

**Product Code:** iieelg

**Dimensions:**  $0.00 \times 0.00 \times$ 

0.00

Price: 0.00 zł

Ex Tax: 0.00 zł

## **Product link**

Link: Swing pump Rexroth A4VG28DWDT1/32R-NZC10F013D-S

R902023012

## **Description**

Axial piston variable pump A4VG. Geometric displacement  $28 \text{ cm}^3$ . Pressure cut-off. Series 3, index 2. Direction of rotation (viewed on drive shaft): clockwise. Sealing material: NBR (nitrile rubber), shaft seal in FKM (fluoroelastomer). Splined shaft DIN 5480 for single pump. Mounting flange SAE J744 2-hole. SAE working port A and B, same side right. Suction port S bottom. Integrated boost pump. Flange SAE J744 82-2 (A), hub for splined shaft 5/8 in 9T 16/32DP. High-pressure relief valve, direct operated, fixed setting 250 to 420 bar without bypass. Filtration in the boost pump pressure line. Ports for external boost circuit filtration ( $F_e$  and  $F_a$ ).

Basic	
Condition	secondhand
Part no.	R902023012

## **Product Gallery**



