## Hydraulic pump Rexroth A4V G40DA1D2/32R-NAC02F025ST R902084522



**Weight: 26.00** 

**Product Code:** Idlhhx **Dimensions:** 0.00 x 0.00 x

0.00

Price: 0.00 zł

Ex Tax: 0.00 zł

## **Product link**

Link: Hvdraulic pump Rexroth A4VG40DA1D2/32R-NAC02F025ST

R902084522

## **Description**

Axial piston variable pump A4VG. Geometric displacement 40 cm<sup>3</sup>. Automatic control, speed related U = 12 V. Pressure cut-off. DA control valve, fixed setting. Series 3, index 2. Direction of rotation (viewed on drive shaft): clockwise. Sealing material: NBR (nitrile rubber), shaft seal in FKM (fluoroelastomer). Splined shaft DIN 5480 for combination pump – 1st pump. Mounting flange SAE J744 2-hole. SAE working port A and B, top and bottom Suction port S bottom. Integrated boost pump. Flange SAE J744 101-2 (B), hub for splined shaft 7/8 in 13T 16/32DP. High-pressure relief valve, direct operated, fixed setting 250 to 420 bar with bypass. Filtration in the boost pump suction line.

Basic	
Condition	used
Part no.	R902084522