Phone: +48 33 870 42 00 - Email: biuro@wibako.pl

## Hydraulic motor Rexroth Rexroth A6VM080DA0000007 C/65MWV0N4Z81D0-0 R902260027



**Weight:** 38.20

**Product Code:** 16tb3tv **Dimensions:** 0.00 x 0.00 x

0.00

Price: 0.00 zł

Ex Tax: 0.00 zł

## **Product link**

Link: Hydraulic motor Rexroth Rexroth

A6VM080DA0000007C/65MWV0N4Z81D0-0 R902260027

## Description

Axial piston variable motor A6VM Series 65. Geometric displacement 080 cm³. Control device: automatic control, speed related, hydraulic travel direction valve. Without pressure control/override. Without solenoid. Without additional function. Damping one-sided in outlet from large stroking chamber. Setting range for displacement: Without  $V_{g\,max}$  setting screw, long (0-adjustable)  $V_{g\,min}$  setting screw. Metric, port threads with O-ring sealing according to ISO 6149. Sealing material: FKM (fluoroelastomer). Standard shaft bearing. Mounting flange ISO 3019-2 140-4. Splined shaft W35×2×16×9g. SAE working ports A and B at rear. With flushing and boost pressure valve, mounted flushing on both sides, flushing flow at:  $\Delta p = p_{ND} - p_{G} = 25$  bar and  $v = 10~\text{mm}^2/\text{s}$  ( $p_{ND} = \text{low pressure}$ ,  $p_{G} = \text{case pressure}$ ). Flushing flow: 10. Without speed sensor. Standard version .

Basic	
Condition	new
Part no.	R902260027

## **Product Gallery**

