

# Hydraulic motor Rexroth Rexroth A6VM080DA0000007 C/65MWV0N4Z81D0-0 R902260027



**Weight:** 38.20

**Product Code:** 16tb3tv

**Dimensions:** 0.00 x 0.00 x  
0.00

**Price:** 0.00 zł

**Ex Tax:** 0.00 zł

## Product link

Link: [Hydraulic motor Rexroth Rexroth A6VM080DA0000007C/65MWV0N4Z81D0-0 R902260027](#)

## Description

Axial piston variable motor A6VM Series 65. Geometric displacement 080 cm<sup>3</sup>. Control device: automatic control, speed related, hydraulic travel direction valve. Without pressure control/override. Without solenoid. Without additional function. Damping one-sided in outlet from large stroking chamber. Setting range for displacement: Without  $V_{g \max}$  setting screw, long (0-adjustable)  $V_{g \min}$  setting screw. Metric, port threads with O-ring sealing according to ISO 6149. Sealing material: FKM (fluoroelastomer). Standard shaft bearing. Mounting flange ISO 3019-2 140-4. Splined shaft W35×2×16×9g. SAE working ports A and B at rear. With flushing and boost pressure valve, mounted flushing on both sides, flushing flow at:  $\Delta p = p_{ND} - p_G = 25$  bar and  $v = 10$  mm<sup>2</sup>/s ( $p_{ND}$  = low pressure,  $p_G$  = case pressure). Flushing flow: 10. Without speed sensor. Standard version .

Basic	
Condition	new
Part no.	R902260027

**Product Gallery**

