

# Hydraulic pump Rexroth A4V G56EP2DT1/32L-NZC02F025F R902021414



**Weight:** 42.00

**Product Code:** usrpas

**Dimensions:** 0.00 x 0.00 x  
0.00

**Price:** 0.00 zł

**Ex Tax:** 0.00 zł

## Product link

Link: [Hydraulic pump Rexroth A4VG56EP2DT1/32L-NZC02F025F R902021414](#)

## Description

Axial piston variable pump A4VG. Geometric displacement 56 cm<sup>3</sup>. Pressure cut-off. Stroking chamber pressure port X<sub>3</sub>, X<sub>4</sub>. Without DA control valve. Series 3, index 2. Direction of rotation (viewed on drive shaft): counter-clockwise. Sealing material: NBR (nitrile rubber), shaft seal in FKM (fluoroelastomer). Splined shaft DIN 5480 for single pump. Mounting flange SAE J744 2-hole. SAE working port A and B, top and bottom Suction port S bottom. Integrated boost pump. Flange SAE J744 101-2 (B), hub for splined shaft 7/8 in 13T 16/32DP. High-pressure relief valve, direct operated, fixed setting 250 to 420 bar with bypass. Filtration in the boost pump pressure line. Attachment filter with cold start valve.

Basic	
Condition	reconditioned
Part no.	R902021414

## Product Gallery

