

# Hydraulic pump Rexroth A4V G56ET5D1/32R-NSC02F045SP R902250864



**Weight:** 42.80

**Product Code:** 1fp2bau

**Dimensions:** 0.00 x 0.00 x  
0.00

**Price:** 0.00 zł

**Ex Tax:** 0.00 zł

## Product link

Link: [Hydraulic pump Rexroth A4VG56ET5D1/32R-NSC02F045SP R902250864](#)

## Description

Axial piston variable pump A4VG. Geometric displacement 56 cm<sup>3</sup>. Electric control, direct operated, two pressure reducing valves U = 12 V. Pressure cut-off. Without DA control valve. Series 3, index 2. Direction of rotation (viewed on drive shaft): clockwise. Sealing material: NBR (nitrile rubber), shaft seal in FKM (fluoroelastomer). Splined shaft ANSI B92.1a for single pump. Mounting flange SAE J744 2-hole. SAE working port A and B, top and bottom Suction port S bottom. Integrated boost pump. Flange SAE J744 101-2 (B), hub for splined shaft 1 in 15T 16/32DP. High-pressure relief valve, direct operated, fixed setting 250 to 420 bar with bypass. Filtration in the boost pump suction line. DEUTSCH molded connector, 2-pin without suppressor diode.

## Basic

Condition	new
-----------	-----

Part no.

R902250864

## Product Gallery

