## Hydraulic pump Rexroth A4V G56ET5D1/32R-NSC02F045SP R902250864



**Weight:** 43.00

**Product Code:** 1fp3bau **Dimensions:** 0.00 x 0.00 x

0.00

Price: 0.00 zł

Ex Tax: 0.00 zł

## **Product link**

Link: Hydraulic pump Rexroth A4VG56ET5D1/32R-NSC02F045SP

R902250864

## **Description**

Axial piston variable pump A4VG. Geometric displacement 56 cm<sup>3</sup>. Electric control, direct operated, two pressure reducing valves U = 12 V. Pressure cut-off. Without DA control valve. Series 3, index 2. Direction of rotation (viewed on drive shaft): clockwise. Sealing material: NBR (nitrile rubber), shaft seal in FKM (fluoroelastomer). Splined shaft ANSI B92.1a for single pump. Mounting flange SAE J744 2-hole. SAE working port A and B, top and bottom Suction port S bottom. Integrated boost pump. Flange SAE J744 101-2 (B), hub for splined shaft 1 in 15T 16/32DP. High-pressure relief valve, direct operated, fixed setting 250 to 420 bar with bypass. Filtration in the boost pump suction line. DEUTSCH molded connector, 2-pin without suppressor diode.

Basic	
Condition	new

R902250864